

# Magellan® 8100

Economical Slim Line Scanner & Scanner/Scale



## Features:

- Efficient and ergonomic 360° Scan Volume
- Patented All-Weights™ Platter
- FirstStrike™ Advanced Decoding Software
- Flash Memory for easy upgrades
- Powered auxiliary RS232 port for easy integration of a handheld scanner
- Host diagnostic reporting
- Optional RSS decoding
- Optional EAS functionality

## High Performance Scanning For The Point-Of-Sale (POS)

The Magellan® 8100 scanner and Magellan® 8100 scanner/scale are entry level members of PSC's high-performance Magellan® line for large volume, point-of-sale applications. They feature PSC's patented 360-degree scan pattern for ergonomically correct scanning when seated or standing. In addition, the Magellan 8100 uses the patented All-Weights™ platter for reducing shrink. Select from five different Magellan® 8100 models to fit your particular application and checkstand designs.

Every Magellan® 8100 also includes FirstStrike™, PSC's advanced decoding software for reading torn, poorly printed and disfigured labels of all types. FirstStrike has the ability to autodiscriminate all supported symbologies for added flexibility and features optional support for Reduced Space Symbology (RSS).

## Versatility By Design

The Magellan® 8100 has a powered auxiliary RS232 port for integrating a PSC handheld scanner for those large or heavy items that are often left in the shopping cart. This port can also be used to update the scanner's software in Flash Memory. Additionally, the Magellan® 8100 can be equipped for full electronic article surveillance (EAS) functionality, including Interlock, for one step scanning and security tag deactivation.

Adding even more value to the POS environment, the Magellan® 8100 features host diagnostic reporting software. This software is used to monitor and report the scanner's health to its host. It can prevent scanner downtime by quickly warning management of potential problems before they actually happen.

## Easy POS Integration

Since the Magellan® 8100 is from PSC you can count on easy installation and years of worry free operation. The Magellan® 8100 has the same familiar form factor as the Magellan SL® so it installs easily into both new and existing point-of-sale configurations. It also supports industry standard host terminal interfaces, including RS232, IBM 46XX, and IBM USB. In addition, the Magellan® 8100 is compatible with OPOS and JavaPOS systems allowing for even greater integration flexibility at the point-of-sale.

*"Nothing Beats a Magellan®"*



# Specifications

Magellan® 8100

## Mechanical

### Length & Weight

Model 8100 (short scanner)  
13.9" / 35.3 cm & 13.0 lbs. / 5.9 kg  
Model 8101 (medium scanner)  
15.7" / 39.9 cm & 15.0 lbs. / 6.9 kg  
Model 8102 (medium scanner/scale)  
15.7" / 39.9 cm & 18.0 lbs. / 8.2 kg  
Model 8103 (long scanner)  
20.0" / 50.8 cm & 15.0 lbs. / 6.9 kg  
Model 8104 (long scanner/scale)  
20.0" / 50.8 cm & 20.0 lbs. / 9.1 kg

Width: 11.5" / 29.2 cm

Depth (below counter): 4.0" / 10.2 cm

Height (above counter): 5.1" / 13.0 cm

### Scale Capacities

Capacity: 30.0 lbs. / 9.99 kg – 15 kg  
(interface dependent)  
Minimum increment: 0.01 lb. / 0.005 kg  
Vibration immunity: 4 programmable  
filter settings  
Maximum static weight: 150 lbs. / 68 kg  
Adjustments required: Calibration only

## Optical

Scan lines: 48  
Motor speed: 4500 rpm  
Scan rate: 3,600 lines/sec.  
Scan zone: 360°  
Sides read: 5  
Read height: 6.0" / 15.2 cm

## Environmental

### Temperature rating

Operating: 50° to 104° F / 10° to 40° C

Storage: -40° to 158° F / -40° to 70° C

Humidity: 5 to 95% NC

## Electrical

### AC Power requirements:

100-250 VAC, 50-60 Hz; 8 Watts (nominal),

12 Watts (maximum), 4 Watts (sleep mode)

## Decoding Capability

*The Magellan® 8100 autodiscriminates between the following supported symbologies:*

UPC Versions A & E

UPC Supplementals (Bookland & Coupon Code)

UPC Add-ons (sub 2 or P2, sub 5 or P5 & C128)

Reduced Space Symbology – *Optional*

(RSS-14, expanded and stacked)

EAN 8, 13

JAN 8, 13

EAN/JAN two label

UCC/EAN 128

Code 39 (with full ASCII)

Code 128

Code 93

12 of 5

Italian Pharmacode

Codabar/NW7

MSI/Plessey

## Communications

Host: IBM 46XX, Single & Dual Cable RS232, IBM USB

Other: Powered RS232 auxiliary port; scale host port; remote scale display port; EAS interlock port

## Safety / Regulatory

Electrical: AS/NZS 60950 (Australia); CSA-C22.2 No.60950 (Canada); EN60 950 (TÜV Europe); PSE Mark (Japan); UL 60950 (USA)

Emissions: FCC part 15, Class B (USA); AS/NZS 3548 (Australia/New Zealand); EN 55022-B (Europe); VCCI-B (Japan)

Laser safety: Class IIa Laser Product



(CAUTION: Laser Light – do not stare into beam); IEC 825 Class 1, EN60 825 Class (Europe)

Weights and measures: Australia; Canada; 90/384/EEC (Europe); Mexico; New Zealand; USA (NIST Handbook 44)

Contact your PSC representative for certification schedule and additional listings.

## Other

EAS compatibility: Integrated EAS hardware will work with Counterpoint IV, V, VI, and VII models available from Checkpoint® Systems.

Good read acknowledgement with Sensormatic.



## PSC Inc.

959 Terry Street  
Eugene OR 97402-9150 USA  
Tel: 800 695 5700 or 541 683 5700  
Fax: 541 345 7140

## Specifications are subject to change without notice.

Additional information concerning this product or other PSC products and services can be found at the PSC website: [www.pscnet.com](http://www.pscnet.com), or contact your PSC representative for more information.



## PSC Worldwide Sales and Service locations

Australia - NSW Tel: 61 2 9878 8999 Fax: 61 2 9878 8688	Australia Tel: 61 3 9281 3288 Fax: 61 3 9243 5510	Belgium Tel: 32 2 414 74 09 Fax: 32 2 410 11 63	Brazil Tel: 55 11 5507 7721 Fax: 55 11 5507 7696	Chile Tel: 562-339-7000 Fax: 562-339-7985	China Tel: 86 10 6857 9048 Fax: 86 10 6857 8699	China - South Tel: 86 20 8765 9955 Fax: 86 20 8765 9955	France Tel: 33 1 64 86 71 00 Fax: 33 1 64 46 72 44
Germany Tel: 49 6151 93580 Fax: 49 6151 935897	Hong Kong Tel: 852 258 46210 Fax: 852 25210291	India Tel: 91 11 24621586 Fax: 91 11 24641662	Italy Tel: 39 039 629031 Fax: 39 039 6859496	Japan Tel: 81 3 3491 6761 Fax: 81 3 3491 6656	Latin America Tel: 1 305 539 0111 Fax: 1 305 539 0206	Singapore Tel: 65 435 1311 Fax: 65 226 1242	Spain Tel: 34 91 746 28 60 Fax: 34 91 742 35 33
Sweden Tel: 46 4010 84 92 Fax: 46 4010 84 91	United Kingdom Tel: 44 1923 809500 Fax: 44 1923 809505						